



4 Type

- C with tapped hole, no bush
- E with taped bush

d ₁	d ₂ KU Type C Thread			KT Type C Thread		d ₃ KU Type E Thread		KT Type E Thread	d ₄ ≈	h	t ₁ min.	t ₂ min.
12	M 4	-	-	-	-	-	-	-	6	11,2	6	-
16	M 4	M 5	-	M 4	M 5	M 4**	-	-	8	15	6	6
20	M 5	M 6	-	M 5	M 6	M 5	-	M 5	12	18	7,5	7,5
25	M 5	M 6	M 8	M 6	M 8	M 6	M 8*	M 6	15	22,5	9	9
30	M 8	-	-	-	-	-	-	-	15	28	12	-
32	M 6	M 8	M 10	M 8	M 10	M 8	-	M 8	18	29	12	12
35	M 10	-	-	-	-	-	-	-	18	32,5	15	-
40	M 8	M 10	M 12	M 10	M 12	M 10	-	-	22	37	15	15
50	M 12	-	-	-	-	M 12	-	-	28	46	18	18

* This size is only available in black with bushing in steel. ** This size is only available in black with bushing in brass.

Specification

- Plastic **KU**
 - Duroplast (Phenolic PF)
 - Flash removed and polished
 - black (standard colour)
 - red **RT**, similar RAL 3003: add RT on order code
- Bush (Type E)
 - Steel, zinc plated (standard)
 - Brass **MS** ad MS on order code

- Plastic **KT**
 - Technopolymer (Polyamide PA)
 - shock resistant
 - black, matt finish (standard colour)
 - red **RT**, similar RAL 3000: add RT on order code
- Bush (Type E)
 - Steel, zinc plated

• RoHS-compliant

Information

- see also...
 - Ball knobs, Press on type DIN 319 → Page 35

How to order

DIN 319-KU-25-M6-C

1	Material
2	d ₁
3	d ₂ (d ₃)
4	Type