



Inch sizes available

1		2		3															
l ₁	d ₁			l ₂								d ₃	d ₄	h ₁	h ₂	h ₃	h ₄	Stroke	
22	M 3	-	-	6	8	10	12	16	-	-	8	10,5	18,5	2	23	3			
22	M 4	M 5	-	12	16	20	25	32	-	-	8	10,5	18,5	2	23	3			
30	M 3	-	-	6	8	10	12	16	-	-	10	13	24,5	4	31	3,5			
30	M 4	-	-	12	16	20	25	32	-	-	10	13	24,5	4	31	3,5			
30	M 5	M 6	-	12	16	20	25	32	40	50	10	13	24,5	4	31	3,5			
45	M 4	-	-	12	16	20	25	32	-	-	10	13	24,5	4	34	3,5			
45	M 5	M 6	-	12	16	20	25	32	40	50	10	13	24,5	4	34	3,5			
63	M 6	M 8	-	16	20	25	32	40	50	63	13,5	17,5	31	6,5	45	4			
78	M 8	M 10	M 12	20	25	32	40	50	63	80	16	21	36	8	54	4			
92	M 10	M 12	-	20	25	32	40	50	63	80	19	24	43	11	64	4			
108	M 12	M 16	-	32	40	50	63	80	-	-	23	30	50,5	12	75	5			

Specification

- Handle
Zinc die casting
- Plastic coated
black, RAL 9005, textured finish
black, RAL 9011, silk finish
orange, RAL 2004, textured finish
red, RAL 3000, textured finish
silver, RAL 9006, textured finish
- chrome-plated
- uncoated
slide grinded
- Threaded stud and retaining screw
Stainless Steel AISI 303
- *Stainless Steel characteristics* → Page 1489
- RoHS

- **SW**
- **SZ**
- **OS**
- **RS**
- **SR**
- **CR**
- **RH**

Information

Adjustable hand levers GN 300.1 are ideal whenever parts have to be clamped in a confined space or in a particular lever position. The centre insert is connected to the lever via serrations which can easily be disengaged.

Pulling the lever, disengages the serrations and allowing it to be swivelled to the ideal clamping position. On releasing the lever the serrations automatically re-engage.

see also...

- *Adjustable hand levers GN 300 (threaded stud steel)* → Page 319
- *Adjustable Stainless Steel-Hand levers GN 300.5 (matte shot-blasted)* → Page 325
- *Adjustable hand levers GN 303.1 (with push button)* → Page 331

How to order

GN 300.1-63-M8-32- RS

1	l ₁
2	d ₁
3	l ₂
4	Color (Finish)