



1.1  
1.2  
1.3  
1.4

1			2							
$l_1$	$d_1$		$d_3$	$d_4$	$h_1$	$h_2$	$h_3$	$h_4$	Stroke	t min.
22	M 3	M 4	M 5	8	10,5	18,5	2	23	3	5
30	M 4	M 5	M 6	10	13	24,5	4	31	3,5	9
45	M 4	M 5	M 6	10	13	24,5	4	34	3,5	9
63	M 6	M 8	-	13,5	17,5	31	6,5	45	4	11
78	M 8	M 10	-	16	21	36	8	54	4	14
92	M 10	M 12	-	19	24	43	11	64	4	17
108	M 12	M 16	-	23	30	50,5	12	75	5	22

2.1

**Specification**

- Handle  
Zinc die casting
- Plastic coated  
black, RAL 9005, textured finish **SW**  
orange, RAL 2004, textured finish **OS**  
red, RAL 3000, textured finish **RS**  
silver, RAL 9006, textured finish **SR**
- chrome-plated **CR**
- uncoated slide grinded **RH**
- Bushing and retaining screw  
Steel  
zinc plated, blue passivated
- ISO-Fundamental tolerances → Page 1479
- RoHS compliant

3

**Information**

Adjustable hand levers GN 300.2 are ideal whenever parts have to be clamped in a confined space or in a particular lever position. The centre insert is connected to the lever via serrations which can easily be disengaged.

Pulling the lever, disengages the serrations and allowing it to be swivelled to the ideal clamping position. On releasing the lever the serrations automatically re-engage.

see also...

- Adjustable hand levers GN 300 (bushing steel, blackened) → Page 318
- Adjustable hand levers GN 300.1 (bushing Stainless Steel) → Page 320
- Adjustable Stainless Steel-Hand levers GN 300.5 (matte shot-blasted) → Page 324
- Adjustable hand levers GN 303
- (with push button, bushing steel) → Page 328
- Adjustable hand levers GN 303.1 (with push button, bushing Stainless Steel) → Page 330

2.2  
2.3  
2.4

How to order	
1	$l_1$
2	$d_1$
3	Color (Finish)

**GN300.2-78-M10-OS**

