



1 2 3

1		2		3						d ₃	d ₄	h ₁	h ₂	h ₃	h ₄ Stroke	
l ₁	d ₁	l ₂														
22	M 3	-	6	8	10	12	16	-	-	8	10,5	18,5	2	23	3	
22	M 4	M 5	12	16	20	25	32	-	-	8	10,5	18,5	2	23	3	
30	M 4	-	12	16	20	25	32	-	-	10	13	24,5	4	31	3,5	
30	M 5	M 6	12	16	20	25	32	40	50	10	13	24,5	4	31	3,5	
45	M 4	-	12	16	20	25	32	-	-	10	13	24,5	4	34	3,5	
45	M 5	M 6	12	16	20	25	32	40	50	10	13	24,5	4	34	3,5	
63	M 6	M 8	16	20	25	32	40	50	63	13,5	17,5	31	6,5	45	4	
78	M 8	M 10	20	25	32	40	50	63	80	16	21	36	8	54	4	
92	M 10	M 12	20	25	32	40	50	63	80	19	24	43	11	64	4	
108	M 16	-	32	40	50	63	80	-	-	23	30	50,5	12	75	5	

Specification

- Handle
Zinc die casting
- Plastic coated
black, RAL 9005, textured finish ● **SW**
orange, RAL 2004, textured finish ● **OS**
red, RAL 3000, textured finish ● **RS**
silver, RAL 9006, textured finish ● **SR**
- chrome-plated ● **CR**
- uncoated ● **RH**
slide ground
- Threaded stud and retaining screw
Steel
zinc plated, blue passivated
- RoHS

Information

Adjustable hand levers GN 300.2 are ideal whenever parts have to be clamped in a confined space or in a particular lever position. The centre insert is connected to the lever via serrations which can easily be disengaged.

Pulling the lever, disengages the serrations and allowing it to be swivelled to the ideal clamping position. On releasing the lever the serrations automatically re-engage.

see also...

- Adjustable hand levers GN 300 (threaded stud steel, blackened) → Page 319
- Adjustable hand levers GN 300.1 (threaded stud St. Steel) → Page 321
- Adjustable Stainless Steel-Hand levers GN 300.5 (matte shot-blasted) → Page 325
- Adjustable hand levers GN 303 (with push button, threaded stud steel) → Page 329
- Adjustable hand levers GN 303.1 (with push button, threaded stud Stainless Steel) → Page 331

How to order

1	l ₁
2	d ₁
3	l ₂
4	Color (Finish)

GN300.2-63-M6-25-RS

1.1
1.2
1.3
1.4
2.1
2.2
2.3
2.4