



**Information**

Stainless Steel-Cabinet "U" handles GN 426.5 can be mounted from the back (type A) as well as from the operator's side (type B). In this case the stud is first screwed in from the machine side and then the handle is pushed on and secured with the grub screw.

Both mounting methods allow the mounting of a pair of handles in opposite position. This method could be used e.g. on doors (double handle). In general, a mounting stud with special length  $l_2$  might be required.

The manufacturing process (bending) allows the production of special lengths in relatively small quantities.

Standard Elements	Main dimensions										Weight
	Description	$d_1$	$l_1 \pm 0.5$	$l_1 \pm 0.3$	$d_2$	$d_3$	h	$l_2$	r	$t_1$	
GN 426.5-20-200-A	20	200	-	M 8	-	68	20	22	15	-	690
GN 426.5-20-250-A	20	250	-	M 8	-	68	20	22	15	-	730
GN 426.5-20-300-A	20	300	-	M 8	-	68	20	22	15	-	960
GN 426.5-20-350-A	20	350	-	M 8	-	68	20	22	15	-	1080
GN 426.5-28-250-A	28	250	-	M 10	32	90	20	32	-	17	550
GN 426.5-28-300-A	28	300	-	M 10	32	90	20	32	-	17	625
GN 426.5-28-350-A	28	350	-	M 10	32	90	20	32	-	17	690
GN 426.5-28-400-A	28	400	-	M 10	32	90	20	32	-	17	730
GN 426.5-20-200-B	20	-	200	M 8	-	68	20	22	15	-	706
GN 426.5-20-250-B	20	-	250	M 8	-	68	20	22	15	-	829
GN 426.5-20-300-B	20	-	300	M 8	-	68	20	22	15	-	957
GN 426.5-20-350-B	20	-	350	M 8	-	68	20	22	15	-	1086
GN 426.5-28-250-B	28	-	300	M 10	32	90	20	32	-	17	625
GN 426.5-28-300-B	28	-	300	M 10	32	90	20	32	-	17	690
GN 426.5-28-350-B	28	-	350	M 10	32	90	20	32	-	17	740
GN 426.5-28-400-B	28	-	400	M 10	32	90	20	32	-	17	820



ELESA and GANTER models all rights reserved in accordance with the law. Always mention the source when reproducing our drawings.

STANDARD MACHINE ELEMENTS WORLDWIDE