



EDELSTAHL®
Rostfrei
Inox
Stainless
Steel

4 Type (Base plate)

- D0** without rubber underlay
- D1** with rubber underlay, clipped on, black
- D3** with rubber underlay, vulcanized, black

d ₁	d ₂	l ₁	Version S / SK				Version T / TK				
50	M 8	40	50	63	-	-	-	-	-	-	
50	M 10	50	60	80	100	-	-	-	-	-	
50	M 12	60	80	100	125	-	-	-	-	-	
50	M 16	-	-	-	-	75	100	125	150	200	
60	M 8	40	50	63	-	-	-	-	-	-	
60	M 10	50	60	80	100	-	-	-	-	-	
60	M 12	60	80	100	125	-	-	-	-	-	
60	M 16	-	-	-	-	75	100	125	150	200	
80	M 8	40	50	63	-	-	-	-	-	-	
80	M 10	50	60	80	100	-	-	-	-	-	
80	M 12	60	80	100	125	-	-	-	-	-	
80	M 16	-	-	-	-	75	100	125	150	200	
80	M 20	-	-	-	-	75	100	125	150	200	
80	M 24	-	-	-	-	100	125	150	200	-	

* not available in type B0

Versions of threaded stem

	<p>5</p> <p>S without nut SK with nut</p>		<p>5</p> <p>T without nut TK with nut</p>
<p>External hexagon at the bottom at d_2 M 8, M 10, M 12</p>		<p>Wrench flat at the bottom at d_2 M 16, M 20, M 24</p>	

d_1	d_2	d_3	h_1	h_3	h_4	h_6	l_8	m	r	s	A/F ₁	A/F ₂
50	M 8 M 10 M 12	6,6	2,5	11	-	4	60	45	15	2	17	-
50	M 16 - -	6,6	2,5	-	17	4	60	45	15	2	-	12
60	M 8 M 10 M 12	6,6	2,5	11	-	4,5	75	50	15	2	17	-
60	M 16 - -	6,6	2,5	-	17	4,5	75	50	15	2	-	12
80	M 8 M 10 M 12	8,5	3	12	-	5	85	70	15	2	17	-
80	M 16 - -	8,5	3	-	18	5	85	70	15	2	-	12
80	M 20 - -	8,5	3	-	19	5	85	70	15	2	-	15
80	M 24 - -	8,5	3	-	22	5	85	70	15	2	-	19

Specification

- Base plate
Stainless Steel
- AISI 316 L (A4)
- blank, ground
- Threaded stem
Stainless Steel AISI 316 L (A4)
- Hexagon nut ISO 4032
Stainless Steel, A4
- Rubber cap
- clipped on
- black, Santoprene® (TPE)
≈ 80 Shore A
- Rubber underlay
- vulcanized
- black, Perbunan® (NBR)
70±5 Shore A
- *Stainless Steel characteristics* → Page 1489
- *Elastomer characteristics* → Page 1483
- *Load rating information* → Page 1474
- **RoHS compliant**

Information

GN 45 Stainless Steel-Levelling feet are for use in aggressive environments. The range of combinations of base plates and adjustable spindle versions allows these levelling feet to be used in every situation.

The levelling feet can be screwed to the mounting surface use the fixing lug, which prevents lateral shifting. Moreover, the types with the rubber underlay protect sensitive surfaces.

The levelling feet are supplied fully assembled and are not removable.

see also...

- *Levelling feet GN 40 (Steel, without fixing lug)* → Page 1040
- *Levelling feet GN 42 (Steel, with fixing lug)* → Page 1040
- *Stainless Steel-Levelling feet GN 41 (without fixing lug)* → Page 1042
- *Stainless Steel-Levelling feet GN 43 (A2, with fixing lug)* → Page 1042
- *Stainless Steel-Levelling feet GN 44 (A4, without fixing lug)* → Page XYZ

<p>How to order</p> <p>GN 45-50-M10-60-D3-SK</p>	1	d_1
	2	d_2
	3	l_1
	4	Type (Base)
	5	Version (Screw)