

Cabinet U-handles

Aluminium

SPECIFICATION

Aluminium

plastic coated

black, RAL 9005, UV-resistant, textured finish **SW**

red, RAL 3000, textured finish **RS**

silver, RAL 9006, textured finish **SR**

black, RAL 9005 antibacterial **SMA**

white, RAL 9016, antibacterial **WSA**

anodized, natural colour **EL**

blank, tumbled **BL**

INFORMATION

GN 565 cabinet U-handles are manufactured from a bent aluminum profile and have excellent stability and ergonomic design. Due to the manufacturing process, **special designs** can be supplied even in relatively small quantities.

In addition to the standard surfaces, these cabinet U-handles are also available with a functional coating.

The **SW** version is coated with a highly weather-resistant and UV-resistant powder coating system, making this version excellent for outdoor use.

The **SMA / WSA** versions have a powder coating based on zinc molybdate, which gives it antibacterial properties. The principle of action, which is activated by the presence of moisture, demonstrably reduces the growth of bacteria within 24 hours, so that contaminated surfaces ultimately have less than 0.2% of the original number of microbes.

Standard elements with antibacterial plastic coating are primarily used in the health care sector and in public buildings, such as airports, train stations, stadiums, etc.

TECHNICAL INFORMATION

- Load rating information (see page A35)

* Complete with colour index of the Cabinet U-handles (SW, RS, SR, SMA, WSA, EL or BL)

SW	RS	SR	SMA	WSA	EL	BL
RAL 9005	RAL 3000	RAL 9006	RAL 9005, antibacterial	RAL 9016, antibacterial	anodized	blank

GN 565

Description	b	l ±0.25	a	d	h	r	t min.	⚖
GN 565-20-100-*	20	100***	13	M 6	49	13	10	87
GN 565-20-112-*	20	112***	13	M 6	49	13	10	93
GN 565-20-117-*	20	117	13	M 6	49	13	10	100
GN 565-20-120-*	20	120**	13	M 6	49	13	10	107
GN 565-20-128-*	20	128***	13	M 6	51	13	10	114
GN 565-20-160-*	20	160***	13	M 6	51	13	10	121
GN 565-20-180-*	20	180**	13	M 6	51	13	10	128
GN 565-20-200-*	20	200	13	M 6	51	13	10	150
GN 565-20-235-*	20	235**	13	M 6	51	13	10	172
GN 565-26-112-*	26	112	17	M 8	55	17	12	161
GN 565-26-117-*	26	117	17	M 8	55	17	12	166
GN 565-26-120-*	26	120**	17	M 8	55	17	12	171
GN 565-26-125-*	26	125	17	M 8	55	17	12	180
GN 565-26-128-*	26	128***	17	M 8	55	17	12	189
GN 565-26-160-*	26	160***	17	M 8	57	17	12	210
GN 565-26-179-*	26	179	17	M 8	57	17	12	234
GN 565-26-192-*	26	192***	17	M 8	57	17	12	245
GN 565-26-300-*	26	300***	17	M 8	57	17	12	345
GN 565-26-400-*	26	400	17	M 8	57	17	12	440
GN 565-26-500-*	26	500	17	M 8	57	17	12	538

** suitable for 19" rack and enclosure layout

*** Sizes also available for type WSA and SMA

