

Retaining magnets

rectangular-shaped, with female thread,
with rubber jacket

SPECIFICATION

Types

- Type **A**: with 1 female thread
- Type **B**: with 2 female threads

Steel part
zinc plated

Material of the magnet
NdFeB
Neodymium, iron, boron
temperature resistant up to 80 °C

Rubber jacket
Elastomer (TPE)
≈ 80 Shore A
black **SW**
white **WS**

INFORMATION

The retaining magnets GN 57.1 with rubber jacket form a system together with the steel part that shields and strengthens the magnet, optimally concentrating the magnetic flux on the rubberized magnetic surface.

The rubber protects sensitive surfaces from being damaged by the magnet and also delivers a high friction coefficient, resulting in high lateral displacement forces.

TECHNICAL INFORMATION

- Elastomer characteristics (see page A32)

ACCESSORY


- Holding discs GN 70 (see page 2051)
- Adhesive discs GN 70.1 (see page 2051)

ON REQUEST




- other colors
- other Shore hardnesses



Type A



Type B



GN 57.1

Description	b	l1	d1	d2	h1	h2	l2	t	Nominal magnetic forces in N	⚖️
GN 57.1-31-43-M4-A-SW	31	43	M 4	10	6	1	-	4.5	105	27
GN 57.1-31-43-M4-A-WS	31	43	M 4	10	6	1	-	4.5	105	27
GN 57.1-31-43-M4-B-SW	31	43	M 4	10	6	1	25	4.5	146	28
GN 57.1-31-43-M4-B-WS	31	43	M 4	10	6	1	25	4.5	146	28

