



- 1 Type**
- SK** Star knob DIN 6335  
Plastic (KU)  
Duroplast (PF)
  - ST** Star knob DIN 6335  
Plastic (KT)  
Technopolymer
  - TE** Star knob GN 6335.2  
Plastic  
Technopolymer
  - SG** Star knob DIN 6335  
Cast iron (GG)

d <sub>1</sub>	d <sub>2</sub>	Length l Type ST, TE							Length l Type SK, SG					
		16	20	25	30	35	45	16	20	25	30	35	45	
32	M 6	16	20	25	30	35	45	16	20	25	30	35	45	
40	M 8	16	20	25	30	40	55	15	20	25	30	40	55	
50	M 10	25	30	35	45	55	-	25	30	35	45	55	-	
63	M 12	30	35	40	50	60	-	30	35	40	50	60	-	
80	M 16	-	-	-	-	-	-	30	40	50	60	70	-	

**Specification**

- Star knob details and dimensions see:
  - DIN 6335-KU / KT
  - GN 6335.2
  - DIN 6335-GG
- For Type SK, ST, TE the threaded bolts are zinc plated, blue passivated and moulded in position
- For Type SG the threaded bolt (blackened) is screwed in and secured by a cross-dowel
- Plastic characteristics
- RoHS compliant

**Information**

Should clamping with the bush face be necessary, then it is recommendable to use either type TE or type SG.

**How to order**

**GN6335.4-SK-63-M12-50**

<b>1</b>	Type
<b>2</b>	d <sub>1</sub>
<b>3</b>	d <sub>2</sub>
<b>4</b>	Length l