



1	2	3			4								
d ₁	d ₂	l ₁			d ₃	d ₄	d ₅	h ₁	h ₂	l ₂	l ₃	l ₄	
32	M 6	25	35	45	15	14	4,5 ±0,03	20	10	5,1	3,6	7,6	
40	M 8	30	40	50	18	18	6,1 ±0,05	25	13	6,2	4,2	9,2	
40	M 8	30	40	50	21	18	6,1 ±0,05	25	13	6,2	5	10	
40	M 8	30	40	50	25	18	6,1 ±0,05	25	13	6,2	5,5	10,5	
40	M 8	30	40	50	32	18	6,1 ±0,05	25	13	6,2	6	11	
50	M 10	35	45	55	21	22	7,8 ±0,05	32	17	7,3	4,3	10	
50	M 10	35	45	55	25	22	7,8 ±0,05	32	17	7,3	4,6	10,5	
50	M 10	35	45	55	32	22	7,8 ±0,05	32	17	7,3	5	11	
50	M 10	35	45	55	40	22	7,8 ±0,05	32	17	7,3	7	13	

Specification

- Star knob DIN 6336
Plastic
Technopolymer (Polyamide PA)
black, matt
- Threaded stud
Stainless Steel
German Material No. 1.4567
- Thrust pad
Plastic
Technopolymer (Polyacetal POM)
- temperature resistant up to 80 °C
- black, matt
- RoHS compliant

Information

Star knobs GN 6336.11 / GN 6336.12 have a ball pin whose diameter is smaller than the core diameter of the thread.

The movable thrust pad is easily clipped on and taken off.

The thrust pads are supplied disassembled.

see also...

- Ball jointed levelling feet GN 638 (without star knob)
- Knurled thumb screws GN 421.11 / GN 421.12
- Star knobs 6336.10 (with plastic / brass pad)

Star knobs with ball pin

GN 6336.11-40-M8-50

1 d₁
2 d₂
3 l₁

Star knobs with movable thrust pad

GN 6336.12-50-M10-45-25

1 d₁
2 d₂
3 l₁
4 d₃