



**Rost frei**®  
Inox  
Stainless  
Steel

- 4 Type**
- A** Only with retaining ring
  - H** With retaining cable
  - K** With ball chain

d <sub>1</sub>	d <sub>2</sub>	Length l					d <sub>3</sub>	h <sub>1</sub>	h <sub>2</sub>	h <sub>3</sub>	r	s	t min.
		10	15	20	25	30							
25*	M 5	10	15	20	25	12	16	8	2,5	21,2	2,8	-	
32	M 6	16	20	25	30	14	20	10	3,5	22,3	2,8	12	
40	M 8	20	25	30	40	18	25	13	4	29,5	3,2	14	
50	M 10	20	25	30	45	22	32	17	5	34,6	3,8	18	
63	M 12	30	40	50	-	26	40	21	5,5	36,7	3,8	22	

\* This size is only available with threaded stud.

**Specification**

- Star knob DIN 6336  
Plastic  
Technopolymer (Polyamide PA)  
Black, matte finish
- Bushing  
Stainless steel AISI 303
- Threaded stud  
Stainless steel  
- M5 ... M10: 304 Cu  
- M12: AISI 303
- Retaining ring GN 111.6  
Stainless steel AISI 301
- Ball chain GN 111.5 (Type K)  
Stainless steel AISI 301
- Retaining cable GN 111.2 (Type H)  
Stainless steel  
Coated with clear plastic
- *Plastic Characteristics* → Page 2158
- *Stainless Steel Characteristics* → Page 2166
- **RoHS**

**On request**

- Ball chains / Retaining cables with other lengths
- With spiral retaining cable GN 111.4
- Other GN standards with loss protection

**Information**

Star knobs GN 6336.13 can be captive-attached to a base element with the help of a ball chain or a retaining cable.

The star knobs are supplied ready assembled (with retaining ring and ball chain or retaining cable).

see also...

- *Stainless Steel Ball Chains GN 111.5* → Page 1174
- *Retaining Cables GN 111.2* → Page 1176
- *Spiral Retaining Cables GN 111.4* → Page 1175
- *Retaining Rings GN 111.6* → Page 1179
- *Further Star Knobs with Loss Protection GN 111.7* → Page 2084

**How to order (Bushing)**

**GN 6336.13-40-M8-A**

- 1 d<sub>1</sub>
- 2 d<sub>2</sub>
- 4 Type

**How to order (Threaded stud)**

**GN 6336.13-50-M10-30-K**

- 1 d<sub>1</sub>
- 2 d<sub>2</sub>
- 3 Length l
- 4 Type

1.1  
1.2  
1.3  
1.4  
2.1  
2.2  
2.3  
2.4