

Waist shaped Stainless Steel-Knobs

Hygienic Design

SPECIFICATION

Types

- Type **D**: with female thread
- Type **E**: with threaded stud

Stainless Steel

- AISI 316 L (A4)
- matte ($R_a < 0.8 \mu\text{m}$) **MT**
- polished ($R_a < 0.8 \mu\text{m}$) **PL**

Sealing ring

H-NBR **H**

temperature resistant -25 °C to +150 °C

EPDM **E**

temperature resistant -40 °C to +120 °C

- blue
- Hardness 85±5 Shore A
- FDA compliant

INFORMATION



GN 75.6 waist shaped Stainless Steel-Knobs are intended for use in hygienic areas. The sealed mounting surfaces enables mounting without dead spaces; the impervious geometry in combination with the high quality finish prevents the accumulation of dirt and facilitates cleaning.

GN 75.6 waist shaped Stainless Steel-Knobs have a compact and timeless design.



TECHNICAL INFORMATION

- Stainless Steel characteristics (see page A26)
- Elastomer characteristics (see page A32)



GN 75.6

STAINLESS STEEL

Description	d1	d2	d4	d5	h	t min.	⚙️
GN 75.6-20-M5-D-MT-H	20	M 5	14	14.8	24	7	25
GN 75.6-20-M5-D-PL-H	20	M 5	14	14.8	24	7	25
GN 75.6-25-M6-D-MT-H	25	M 6	16	16.8	29	9	45
GN 75.6-25-M6-D-PL-H	25	M 6	16	16.8	29	9	45
GN 75.6-32-M8-D-MT-H	32	M 8	18	18.8	37	12	82
GN 75.6-32-M8-D-PL-H	32	M 8	18	18.8	37	12	83
GN 75.6-20-M5-D-MT-E	20	M 5	14	14.8	24	7	25
GN 75.6-20-M5-D-PL-E	20	M 5	14	14.8	24	7	25
GN 75.6-25-M6-D-MT-E	25	M 6	16	16.8	29	9	45
GN 75.6-25-M6-D-PL-E	25	M 6	16	16.8	29	9	45
GN 75.6-32-M8-D-MT-E	32	M 8	18	18.8	37	12	82
GN 75.6-32-M8-D-PL-E	32	M 8	18	18.8	37	12	83

GN 75.6

STAINLESS STEEL

Description	d1	d3	d4	d5	h	l	⚙️
GN 75.6-20-M5-E-MT-H	20	M 5	14	14.8	24	10	28
GN 75.6-20-M5-E-PL-H	20	M 5	14	14.8	24	10	28
GN 75.6-25-M6-E-MT-H	25	M 6	16	16.8	29	12	50
GN 75.6-25-M6-E-PL-H	25	M 6	16	16.8	29	12	50
GN 75.6-32-M8-E-MT-H	32	M 8	18	18.8	37	14	92
GN 75.6-32-M8-E-PL-H	32	M 8	18	18.8	37	14	93
GN 75.6-20-M5-E-MT-E	20	M 5	14	14.8	24	10	28
GN 75.6-20-M5-E-PL-E	20	M 5	14	14.8	24	10	28
GN 75.6-25-M6-E-MT-E	25	M 6	16	16.8	29	12	50
GN 75.6-25-M6-E-PL-E	25	M 6	16	16.8	29	12	50
GN 75.6-32-M8-E-MT-E	32	M 8	18	18.8	37	14	92
GN 75.6-32-M8-E-PL-E	32	M 8	18	18.8	37	14	93