



3 Bore code

- B without keyway
- K with keyway
- V with square

5 Type

- A without handle
- F with fixed handle
- D with revolving handle

2 d_1	4 d_2 H7 Bore			4 s H11 Square	$d_3 \approx$	d_4	b	l_1	$l_2 \approx$	\emptyset Handle	No. of spokes
80	10	12	-	V 9	24	M 6	14	16	29	16	3
100	10	12	-	V 9	26	M 6	15	17	33	16	3
125	12	14	-	V 11	28	M 8	16	18	36	20	3
140	14	16	-	-	30	M 8	17	19	39	20	3
160	14	15	16	V 12	33	M 10	18	20	40	25	3
180	16	18	-	-	35	M 10	20	22	43	25	3
200	18	20	22	V 14	38	M 10	22	24	45	25	3
250	22	24	26	V 17	48	M 12	26	28	50	32	5
315	26	28	30	V 19	53	M 12	28	33	56	32	5
400	30	32	34	V 24	65	M 12	32	38	63	32	5
500	34	36	40	V 27	78	M 12	34	45	72	32	5

Specification

- Cast iron **GG**
 - Hub machined
 - Rim turned und polished
- Aluminium **AL**
 - Hub machined
 - Rim turned und polished
 - unmachined body shot-blasted
- Rim concentric and square to bore < 0,4
- Handles DIN 39 / DIN 98
 - Steel, zinc plated bzw.
 - Plastic, Technopolymer black
- RoHS compliant

1

Information

Handwheels DIN 950-GG (cast iron) are supplied with revolving handles DIN 98 made of zinc plated steel. Handwheels DIN 950-AL (aluminum) are supplied with revolving handles DIN 98 made of plastic.

see also...

- Countersunk washers GN 184 (for axial fixing)

How to order

1 Material
2 d_1
3 Bore code
4 d_2 (s)
5 Type

DIN 950-GG-160-B14-A