

Mushroom handles

“Soft-touch” technopolymer

MATERIAL

High-resilience polypropylene based (PP) technopolymer coated with “soft-touch” thermoplastic elastomer (TPE) chemically bonded, hardness 70 Shore A, black colour, matte finish.

Raw material coating suitable for contact with food (FDA CFR.21 and EU 10/2011).

STANDARD EXECUTION

Plain blind hole.

The elastic coupling, by press-fit assembly on h9 tolerance drawn stock bars, is not affected by vibrations and prevents the handle from slipping off (see Technical Data on page A13).

FEATURES AND APPLICATIONS


The coating, with “soft-touch” elastomer, improves the grip even in the presence of oils, greases and sweat from the hand. For this reason it is suitable for fitness machines, tools and machines for gardening and goods transport, high-precision instruments and disability aids.

ASSEMBLY INSTRUCTIONS

Fit the handle onto slight chamfered shaft end and push as far as possible by hand or by means of a small press. Alternatively it is possible to tap the handle with a plastic or wooden mallet until firmly in place. In this case we strongly recommend to use a cloth or other suitable soft material over the product to avoid any surface damage.



ELESA Original design



Code	Description	D	L	d	d1	h	⚖
26642	IEL.47 N-12 SOFT	45	47	12	28	34	48
26661	IEL.65 N-10 SOFT	45	65	10	23	50	56
26662	IEL.65 N-12 SOFT	45	65	12	23	50	55
26663	IEL.65 N-14 SOFT	45	65	14	23	30	55