



Heyco® Original Strain Relief Bushings

Straight-Thru for Flat Cables



WILL FIT THESE CABLES				PANEL DIMENSIONS						PART NO.	DESCRIPTION	C		Mounting Hole Plug	
UL Type	AWG/ Conductors	Approximate Size		A Mounting Hole Dia.		B To Prevent Rotation		Finished Fit Panel Thickness*				BODY LENGTH			PART NO.
		in.	mm.	in.	mm.	in.	mm.	in.	mm.	in.	mm.				
SPT-2	18/3	.15 x .40	3,8 x 10,2												
	16/3	.16 x .41	4,1 x 10,4												
SPT-3	18/2	.19 x .35	4,8 x 8,9	.560**	14,2	.730**	18,5	.125	3,2	1484	SR 30-1**	.672	17,1	consult Heyco	
	18/3	.19 x .39	4,8 x 9,9												
	16/2	.20 x .37	5,1 x 9,4												
	16/3	.20 x .43	5,1 x 10,9												
SPT-2	18/3	.15 x .40	3,0 x 7,6	.625	15,9	.550	14,0	.062	1,6	1160	SR 6N4-4	.578	14,7	2497	
	16/3	.16 x .41	4,1 x 10,4												
Same as SR 6N4-4 above except									.125	2,5	1163	SR 6P4-4	.578	14,7	2497
SPT-3	16/2	.20 x .37	5,1 x 9,4	.750**	19,0	.875**	22,2	.125	3,2	1504	SR 33-1**	.781	19,8	consult Heyco	
	16/3	.20 x .43	5,1 x 10,9												
	14/2	.24 x .42	6,1 x 10,7												
	14/3	.24 x .51	6,1 x 12,9												
SPT-3***	14/2	.24 x .42	6,1 x 10,7	.875	22,2	.840	21,3	.125	3,2	1517	SR 34-2	.813	20,7	2509	
	14/3	.24 x .51	6,1 x 12,9												
	12/2	.29 x .51	7,4 x 12,9												
	12/3	.29 x .65	7,4 x 16,5												
SPT-3	12/3 10/3	.32 x .65	8,1 x 16,5	.875	22,2	.835	21,2	.125	3,2	1497	SR 31-2	.812	20,6	2509	

Standard color black. Consult Heyco for white and other colors.

* Maximum Panel Thickness. Part has additional clearance. Consult Heyco for your Custom Finished Fit Panel Thickness.

** Use Elongated Mounting Hole.

*** For Universal Strain Reliefs, see page 4-15. For Romex® Connectors, see pages 4-31 and 4-32.

Straight-Thru for Flat Cables, with Flex-Protecting Internal Radii and Extra Body Length


WILL FIT THESE CABLES				PANEL DIMENSIONS						PART NO.	DESCRIPTION	C		Mounting Hole Plug	
UL Type	AWG/ Conductors	Approximate Size		A Mounting Hole Dia.		B To Prevent Rotation		Finished Fit Panel Thickness*				BODY LENGTH			PART NO.
		in.	mm.	in.	mm.	in.	mm.	in.	mm.	in.	mm.				
SPT-1	18/3	.12 x .30	3,0 x 7,6												
SPT-1 & HPN	18/2	.15 x .28	3,8 x 7,1	.500	12,7	.465	11,8	.040 ***	1,0	1181	SR 4A-6	.546	13,9	2491	
Same as SR 4A-6 above except									.062	1,6	1187	SR 4N-6	.546	13,9	2491
Same as SR 4A-6 above except									.100	2,5	1190	SR 4K-6	.546	13,9	2491

Standard color black. Consult Heyco for white and other colors.


* Maximum Panel Thickness. Part has additional clearance. Consult Heyco for your Custom Finished Fit Panel Thickness.

*** To install Strain Reliefs for .040" (1,0 mm) Maximum Panel Thickness use Part No. 0021 (No. R-291) Hand Pliers.

“DOUBLE D” MOUNTING HOLE



ELONGATED MOUNTING HOLE



Material

6/6 Nylon

Certifications

Recognized under the Component Program of Underwriters' Laboratories File E15331

Certified by the Canadian Standards Association File 8919

Flammability Rating

94V-2

Material Temperature Index

257°F (125°C)–Maximum temperature on part not to exceed 221°F (105°C)

Quick Specs