

**Closed End
Domed Head**

Aluminium 5% Magnesium Alloy
Mandrel: Stainless Steel



			DESCRIPTION							BULK PACK		
										ARTICLE	BOX QTY	
mm	mm	mm		mm	mm	mm	mm	N	N			kg
3.2 3.10 - 3.28	6.0	Up To 1.6	AD42SS	3.3 - 3.4	5.70 - 6.30	1.10	1.63	1,110	1,400	80389	10,000	0.83
	7.5	1.6 - 3.2	AD44SS							80397	10,000	0.86
	9.0	3.2 - 4.8	AD46SS							80406	10,000	0.88
	11.0	4.8 - 6.4	AD48SS							80410	10,000	0.90
	12.5	6.4 - 7.9	AD410SS							80450	10,000	0.93
4.0 3.90 - 4.08	8.0	Up To 3.2	AD54SS	4.1 - 4.2	7.62 - 8.22	1.50	2.18	1,640	2,220	80256	8,000	1.59
	9.5	3.2 - 4.8	AD56SS							80254	8,000	1.61
	11.0	4.8 - 6.4	AD58SS							80253	8,000	1.65
	12.5	6.4 - 7.9	AD510SS							75135	5,000	1.68
4.8 4.73 - 4.88	8.3	Up To 3.2	AD64SS	4.9 - 5.0	9.20 - 9.85	1.75	2.64	2,260	3,110	80431	5,000	2.38
	10.0	3.2 - 4.8	AD66SS							80439	5,000	2.44
	11.5	4.8 - 6.4	AD68SS							80447	5,000	2.48
	13.0	6.4 - 7.9	AD610SS							80463	5,000	2.54
	14.5	7.9 - 9.5	AD612SS							80471	5,000	2.74
	18.0	9.5 - 12.7	AD616SS							80475	4,000	2.98
22.0	12.7 - 15.9	AD620SS	80478	4,000	3.30							

d=Nominal Diameter, Min - Max Diameter; *l*=Body Length (+/- 0.5mm); *g*=Grip Range (Min - Max); *dh*=Hole Size (Min - Max); *dk*=Flange Diameter (Min - Max); *k*=Flange Thickness (Max); *dm*=Nominal Mandrel Diameter; *S*=Nominal Shear Strength; *T*=Nominal Tensile Strength

The POP® Riveting Systems catalogue contains details of our core range only. Other rivet configurations are available. Please enquire to Emhart Customer Service. For the latest catalogue digital version please visit www.emhart.eu