



FOR FINISH DETAILS SEE DRG 300816

PRODUCT CODE		L	GRIP RANGE	
AK 52 H		9.4	1.6 TO 3.2	
AK 53 H		11.0	3.2 TO 4.8	
AK 54 H		12.6	4.8 TO 6.4	
AK 55 H		14.2	6.4 TO 7.9	
AK 56 H		16.0	7.9 TO 9.5	
SHEAR STRENGTH 1640 N		TENSILE STRENGTH 2220 N		HOLE SIZE ϕ 4.1 / 4.2
MATERIAL MANDREL CARBON STEEL BODY ALUMINIUM BS1473 Al Mg 5%				
This drawing is the property of Tucker Fasteners Ltd. It is confidential and must not be lent or copied except by written consent.		TITLE 5 SIZE POP CLOSED END ALUMINIUM ALLOY BLIND RIVET		
		19OCT12	21360	1
ALL DIMENSIONS ARE IN MILLIMETRES		SCALE 3 : 1	DR R.EVERILL	Date 19OCT12
SHEET 1 OF 2		©TUCKER FASTENERS Ltd. EMHART FASTENING TEKNOLOGIES Walsall Road, Birmingham B42 1BP, England. A BLACK & DECKER COMPANY		
A4OPEN	A4			