

Closed End 120° Countersunk

Aluminium 5% Magnesium Alloy
Mandrel: Carbon Steel



d	l	g	DESCRIPTION	d_h	d_k	k	d_m	S	T	BULK PACK		/1,000 kg
										ARTICLE	BOX QTY	
mm	mm	mm		mm	mm	mm	mm	N	N			kg
3.2 3.10 - 3.28	7.0	Up To 2.5	AK42SB	3.3 - 3.4	5.69 - 6.29	-	1.65	1,110	1,400	80493	10,000	0.75
	8.5	2.5 - 4.1	AK44SB							80499	10,000	0.77
	10.0	4.1 - 5.6	AK46SB							80505	10,000	0.80
	11.7	5.6 - 7.2	AK48SB							80508	10,000	0.88
	13.3	7.2 - 8.8	AK410SB							80536	10,000	0.90
4.0 3.90 - 4.08	9.5	Up To 4.4	AK54SB	4.1 - 4.2	7.62 - 8.22	-	2.18	1,640	2,220	80512	8,000	1.59
	11.0	4.4 - 6.0	AK56SB							80516	8,000	1.61
	12.5	6.0 - 7.6	AK58SB							80520	8,000	1.65
	14.0	7.6 - 9.2	AK510SB							80540	5,000	1.68
4.8 4.70 - 4.88	10.0	Up To 4.7	AK64SB	5.0 - 5.1	9.25 - 9.85	-	2.62	2,260	3,110	80524	5,000	2.38
	11.5	4.7 - 6.3	AK66SB							80528	5,000	2.44
	13.0	6.3 - 7.9	AK68SB							80533	5,000	2.48
	14.7	7.9 - 9.4	AK610SB							80544	5,000	2.54
	16.3	9.4 - 11.0	AK612SB							80549	5,000	2.72
	19.5	11.0 - 14.2	AK616SB							80551	4,000	2.93
23.5	14.2 - 18.4	AK620SB	80553	4,000	3.35							

d =Nominal Diameter, Min - Max Diameter; l =Body Length (+/- 0.5mm); g =Grip Range (Min - Max); d_h =Hole Size (Min - Max); d_k =Flange Diameter (Min - Max);
 k =Flange Thickness (Max); d_m =Nominal Mandrel Diameter; S =Nominal Shear Strength; T =Nominal Tensile Strength

The POP® Riveting Systems catalogue contains details of our core range only. Other rivet configurations are available. Please enquire to Emhart Customer Service. For the latest catalogue digital version please visit www.emhart.eu