

Terminal Tag Domed Head

Copper
Mandrel: Carbon Steel (Copper Finish)



			DESCRIPTION									BULK PACK		
					mm	mm	mm	mm	mm			mm	mm	
4.0	5.3	Up To 2.0	PMC46/01	5.15 - 5.20	1	10.5	6.3	8	2.3	1,330	1,910	on request		kg
4.0	5.3	Up To 2.0	PMC2/6.3	5.15 - 5.20	2	21	6.3	8	2.3	1,330	1,910	on request		
	5.3	Up To 2.0	PMC4/6.3		4	42						on request		

Closed End Domed Head

Copper
Mandrel: Carbon Steel



			DESCRIPTION							BULK PACK		
					mm	mm	mm			N	N	
3.2 3.10 - 3.28	6.0	Up To 1.6	CD42SB	3.3 - 3.4	5.70 - 6.30	1.10	1.65	1,020	1,420	75338	10,000	1.08
	7.5	1.6 - 3.2	CD44SB							75339	10,000	1.23
	9.0	3.2 - 4.8	CD46SB							75340	10,000	1.24
	12.3	4.8 - 7.9	CD410SB							75341	10,000	1.46
4.0 3.85 - 4.08	9.5	Up To 4.8	CD56SB	4.1 - 4.2	7.62 - 8.22	1.50	2.18	1,550	2,260	77474	6,000	2.42
	12.7	4.8 - 7.9	CD510SB							75343	5,000	2.58
4.8 4.70 - 4.88	8.5	Up To 3.2	CD64SB	4.9 - 5.0	9.23 - 9.83	1.75	2.64	2,130	3,110	77476	4,000	3.45
	11.5	3.2 - 6.4	CD68SB							77477	4,000	3.82
	13.0	6.4 - 7.9	CD610SB							75346	5,000	3.91
	14.5	7.9 - 9.5	CD612SB							77475	3,000	4.21
	18.0	9.5 - 12.7	CD616SB							on request		4.74

d =Nominal Diameter, Min - Max Diameter; l =Body Length (+/- 0.5mm); g =Grip Range (Min - Max); d_h =Hole Size (Min - Max); d_k =Flange Diameter (Min - Max); k =Flange Thickness (Max); d_m =Nominal Mandrel Diameter; S =Nominal Shear Strength; T =Nominal Tensile Strength; t =Number of Tags; sw =Shoulder Width; tw =Tag Width; tl =Tag Length

The POP® Riveting Systems catalogue contains details of our core range only. Other rivet configurations are available. Please enquire to Emhart Customer Service. For the latest catalogue digital version please visit www.emhart.eu