











PSZRON









HEAD: **Reduced Head** TYPE: **Open End** SECTION: **Round** SURFACE: **Linear Knurls**

|  <i>M</i> |  <i>l</i> |  <i>g</i> | DESCRIPTION |  <i>d_h</i> |  <i>d_k</i> |  <i>k</i> |  <i>d</i> | BULK PACK | | SMALL PACK | |  /1,000 kg |
|---|---|---|---------------------|---|---|---|---|-----------|---------|------------|---------|---|
| | | | | | | | | ARTICLE | BOX QTY | ARTICLE | BOX QTY | |
| mm | mm | mm | | mm | mm | mm | mm | | | | | kg |
| M3 | 9.8 | 0.5 - 2.5 | PSZRON-03025 | 5.0 | 5.8 | 0.6 | 4.9 | 48491 | 10,000 | 48492 | 500 | 0.8 |
| M4 | 10.3 | 0.5 - 3.0 | PSZRON-0430 | 6.0 | 6.8 | 0.6 | 5.9 | 33036 | 10,000 | 33042 | 500 | 0.9 |
| M5 | 11.8 | 0.5 - 3.0 | PSZRON-0530 | 7.0 | 7.8 | 0.6 | 6.9 | 33049 | 10,000 | 33048 | 500 | 1.4 |
| M6 | 14.3 | 0.5 - 3.0 | PSZRON-0630 | 9.0 | 9.8 | 0.6 | 8.9 | 33047 | 4,000 | 33046 | 500 | 3.0 |
| M8 | 15.8 | 0.5 - 3.0 | PSZRON-0830 | 11.0 | 11.8 | 0.6 | 10.9 | 33240 | 2,000 | 33239 | 250 | 4.4 |
| M10 | 19.8 | 0.8 - 3.5 | PSZRON-1035 | 12.0 | 13.3 | 0.8 | 11.9 | 33242 | 2,000 | 33241 | 200 | 6.0 |



PSZRO

HEAD: **Reduced Head** TYPE: **Open End** SECTION: **Round**

|  <i>M</i> |  <i>l</i> |  <i>g</i> | DESCRIPTION |  <i>d_h</i> |  <i>d_k</i> |  <i>k</i> |  <i>d</i> | BULK PACK | | SMALL PACK | |  /1,000 kg |
|---|---|---|-------------------|---|---|---|---|-----------|---------|------------|---------|---|
| | | | | | | | | ARTICLE | BOX QTY | ARTICLE | BOX QTY | |
| mm | mm | mm | | mm | mm | mm | mm | | | | | kg |
| M4 | 10.8 | 0.5 - 3.0 | PSZRO-0430 | 6.1 | 6.5 | 0.5 | 6.0 | 00363 | 10,000 | 08856 | 500 | 1.1 |
| M5 | 12.0 | 0.5 - 3.0 | PSZRO-0530 | 7.1 | 7.5 | 0.5 | 7.0 | 33380 | 5,000 | 09659 | 500 | 1.6 |
| | 15.0 | 3.0 - 5.5 | PSZRO-0555 | | | | | 33382 | 4,000 | 33381 | 500 | 1.8 |
| M6 | 14.5 | 0.5 - 3.0 | PSZRO-0630 | 9.1 | 9.5 | 0.5 | 9.0 | 00364 | 3,000 | 08530 | 500 | 3.4 |
| | 16.5 | 3.0 - 5.5 | PSZRO-0655 | | | | | 33385 | 2,500 | 33384 | 500 | 3.7 |
| M8 | 16.0 | 0.5 - 3.0 | PSZRO-0830 | 11.1 | 11.5 | 0.5 | 11.0 | 00366 | 2,000 | 08937 | 250 | 5.0 |
| | 18.5 | 3.0 - 5.5 | PSZRO-0855 | | | | | 33387 | 1,500 | 33386 | 250 | 5.5 |
| M10 | 19.5 | 0.8 - 3.5 | PSZRO-1035 | 12.5 | 12.9 | 0.5 | 12.4 | 33389 | 1,250 | 33388 | 250 | 6.7 |

M=Thread Size; *l*=Nominal Body Length; *g*=Grip Range (Min - Max); *d_h*=Hole Size; *d_k*=Nominal Head Diameter; *k*=Nominal Head Thickness; *d*=Nominal Barrel Diameter