

## Break Stem Open

### Domed Head

Stainless Steel

Mandrel: Stainless Steel



			DESCRIPTION							BULK PACK		
										ARTICLE	BOX QTY	
mm	mm	mm		mm	mm	mm	mm	N	N			kg
<b>3.2</b> 3.10 - 3.28	4.8	0.8 - 1.6	<b>SSD41SSBS</b>	3.3 - 3.4	6.04 - 6.65	1.10	1.93	2,400	3,000	75234	10,000	1.18
	6.4	1.6 - 3.2	<b>SSD42SSBS</b>							22000	10,000	1.23
	8.0	3.2 - 4.8	<b>SSD43SSBS</b>							22001	10,000	1.30
	9.5	4.8 - 6.4	<b>SSD44SSBS</b>							22002	10,000	1.40
	11.1	6.4 - 7.9	<b>SSD45SSBS</b>							on request		1.46
	12.7	7.9 - 9.5	<b>SSD46SSBS</b>							78525	9,000	1.52
	15.9	9.5 - 12.7	<b>SSD48SSBS</b>							24499	8,000	1.66
<b>4.0</b> 3.88 - 4.08	7.0	1.6 - 3.2	<b>SSD52SSBS</b>	4.1 - 4.2	7.53 - 8.33	1.20	2.41	4,000	5,000	78526	7,000	2.04
	8.6	3.2 - 4.7	<b>SSD53SSBS</b>							on request		2.06
	10.2	3.2 - 6.4	<b>SSD54SSBS</b>							78528	6,000	2.08
	13.3	6.4 - 9.5	<b>SSD56SSBS</b>							78592	5,000	2.56
<b>4.8</b> 4.65 - 4.88	7.6	1.6 - 3.2	<b>SSD62SSBS</b>	4.9 - 5.0	9.06 - 9.98	1.40	2.90	4,400	6,100	78531	4,000	3.20
	10.8	3.2 - 6.4	<b>SSD64SSBS</b>							78534	4,000	3.58
	14.0	6.4 - 9.5	<b>SSD66SSBS</b>							78495	4,000	3.80
	17.2	9.5 - 12.7	<b>SSD68SSBS</b>							78496	3,000	3.98
	20.3	12.7 - 15.9	<b>SSD610SSBS</b>							on request		4.18
	29.7	22.3 - 25.4	<b>SSD616SSBS</b>							on request		4.58

$d$ =Nominal Diameter, Min - Max Diameter;  $l$ =Body Length (+/- 0.5mm);  $g$ =Grip Range (Min - Max);  $d_h$ =Hole Size (Min - Max);  $d_k$ =Flange Diameter (Min - Max);  $k$ =Flange Thickness (Max);  $d_m$ =Nominal Mandrel Diameter;  $S$ =Nominal Shear Strength;  $T$ =Nominal Tensile Strength

The POP® Riveting Systems catalogue contains details of our core range only. Other rivet configurations are available. Please enquire to Emhart Customer Service. For the latest catalogue digital version please visit [www.emhart.eu](http://www.emhart.eu)