

Break Stem Open

Domed Head

Aluminium 3.5% Magnesium Alloy
Mandrel: Carbon Steel



			DESCRIPTION							BULK PACK		
										ARTICLE	BOX QTY	
mm	mm	mm		mm	mm	mm	mm	N	N			kg
2.4 2.30 - 2.48	3.5	Up To 0.8	TAPD31BS	2.5 - 2.6	4.40 - 5.00	0.90	1.42	400	500	23758	10,000	0.53
	5.0	0.8 - 2.4	TAPD33BS							22806	10,000	0.54
	7.5	2.4 - 4.8	TAPD36BS							22807	10,000	0.59
3.0 2.90 - 3.08	5.0	Up To 2.0	SNAD3050BS	3.1 - 3.2	5.70 - 6.30	1.10	1.83	800	1,000	22486	10,000	0.90
	6.5	2.0 - 3.5	SNAD3065BS							22487	10,000	0.94
	8.0	3.5 - 5.0	SNAD3080BS							22489	10,000	1.00
	10.0	5.0 - 7.0	SNAD3100BS							22490	10,000	1.05
	12.0	7.0 - 9.0	SNAD3120BS							22492	8,000	1.29
	15.0	9.0 - 12.0	SNAD3150BS							22493	5,000	1.33
3.2 3.10 - 3.28	4.5	Up To 1.6	TAPD42BS	3.3 - 3.4	6.05 - 6.65	1.10	1.83	800	1,200	20124	10,000	0.87
	6.0	1.6 - 3.2	TAPD44BS							20125	10,000	0.92
	8.0	3.2 - 4.8	TAPD46BS							20127	10,000	0.98
	9.7	4.8 - 6.4	TAPD48BS							20128	10,000	1.04
	11.5	6.4 - 7.9	TAPD410BS							20129	10,000	1.11
	13.5	7.9 - 9.5	TAPD412BS							21196	8,000	1.20
	15.0	9.5 - 11.1	TAPD414BS							20056	8,000	1.26
	17.0	11.1 - 12.7	TAPD416BS							21305	8,000	1.36
	18.5	12.7 - 14.3	TAPD418BS							21519	8,000	1.37
	20.0	14.3 - 16.7	TAPD421BS							77898	7,000	1.47
24.0	16.7 - 20.7	TAPD425BS	25243	5,000	1.65							
4.0 3.90 - 4.08	5.0	Up To 1.6	TAPD52BS	4.1 - 4.2	7.62 - 8.22	1.22	2.29	1,330	1,910	21246	8,000	1.56
	7.0	1.6 - 3.2	TAPD54BS							20130	8,000	1.54
	8.5	3.2 - 4.8	TAPD56BS							20131	8,000	1.63
	10.5	4.8 - 6.4	TAPD58BS							20132	8,000	1.73
	12.2	6.4 - 7.9	TAPD510BS							20133	5,000	1.82
	14.0	7.9 - 9.5	TAPD512BS							20134	5,000	1.90
	15.7	9.5 - 11.1	TAPD514BS							21262	5,000	2.00
	17.5	11.1 - 12.7	TAPD516BS							21250	5,000	2.10
	18.5	12.7 - 13.5	TAPD517BS							75003	5,000	2.28
	19.4	12.7 - 14.5	TAPD518BS							22112	5,000	2.32
	20.2	13.5 - 15.9	TAPD520BS							21186	5,000	2.33
	22.5	15.9 - 17.4	TAPD522BS							25316	5,000	2.56
	24.7	17.4 - 19.8	TAPD525BS							80911	5,000	2.59

d =Nominal Diameter, Min - Max Diameter; l =Body Length (+/- 0.5mm); g =Grip Range (Min - Max); d_h =Hole Size (Min - Max); d_k =Flange Diameter (Min - Max); k =Flange Thickness (Max); d_m =Nominal Mandrel Diameter; S =Nominal Shear Strength; T =Nominal Tensile Strength

The POP® Riveting Systems catalogue contains details of our core range only. Other rivet configurations are available. Please enquire to Emhart Customer Service. For the latest catalogue digital version please visit www.emhart.eu

Break Stem Open Domed Head

Aluminium 3.5% Magnesium Alloy
Mandrel: Carbon Steel



				DESCRIPTION							BULK PACK		
											ARTICLE	BOX QTY	
	mm	mm	mm		mm	mm	mm	mm	N	N			kg
4.8 4.70 - 4.88	6.5	Up To 2.4		TAPD63BS	4.9 - 5.0	9.20 - 9.80	1.60	2.64	2,020	2,800	21313	5,000	2.35
	7.5	2.4 - 3.2		TAPD64BS							20136	5,000	2.16
	9.2	3.2 - 4.8		TAPD66BS							20137	5,000	2.28
	11.0	4.8 - 6.4		TAPD68BS							20138	5,000	2.42
	12.7	6.4 - 7.9		TAPD610BS							20139	5,000	2.56
	14.7	7.9 - 9.5		TAPD612BS							20140	4,000	2.68
	16.5	9.5 - 11.1		TAPD614BS							20141	4,000	2.90
	19.0	11.1 - 13.5		TAPD617BS							21190	4,000	3.05
	21.0	13.5 - 15.5		TAPD621BS							22928	3,000	3.48
	23.0	15.5 - 17.5		TAPD623BS							23248	3,000	3.63
	25.5	17.5 - 19.8		TAPD625BS							22968	3,000	3.47
	32.5	19.8 - 26.2		TAPD633BS							23776	2,000	4.10
5.0 4.94 - 5.08	6.5	Up To 3.5		SNAD5065BS	5.1 - 5.2	8.70 - 9.30	1.60	2.64	2,200	2,600	22976	5,000	2.35
	8.0	3.5 - 4.5		SNAD5080BS							22977	5,000	2.47
	10.0	4.5 - 6.0		SNAD5100BS							22978	5,000	2.62
	12.0	6.0 - 7.5		SNAD5120BS							22979	5,000	2.77
	15.0	7.5 - 9.5		SNAD5140BS							22980	5,000	2.81
	16.0	9.5 - 11.5		SNAD5160BS							22981	5,000	3.04
	19.0	11.5 - 13.5		SNAD5180BS							22982	5,000	3.11
	20.0	13.5 - 15.5		SNAD5200BS							22983	4,000	3.18
	22.0	16.5 - 17.5		SNAD5220BS							22984	3,000	3.55
	25.0	17.5 - 20.5		SNAD5250BS							22985	3,000	3.77
6.0 5.93 - 6.08	8.0	0.5 - 3.5		SNAD6080BS	6.1 - 6.2	11.70 - 12.30	2.10	3.20	3,000	3,800	23387	4,000	4.03
	10.0	3.5 - 5.5		SNAD6100BS							23345	2,000	4.14
	12.0	5.5 - 7.5		SNAD6120BS							23346	2,000	4.58
	15.0	7.5 - 9.5		SNAD6140BS							23347	2,000	4.90
	16.0	9.5 - 11.5		SNAD6160BS							23373	2,000	5.00
	19.0	11.5 - 13.5		SNAD6180BS							23389	2,000	5.25
	20.0	13.5 - 15.5		SNAD6200BS							23354	2,000	5.34
6.4 6.25 - 6.48	12.7	Up To 6.4		TAPD88BS	6.5 - 6.6	12.40 - 13.00	2.10	3.66	3,200	4,525	22941	2,000	5.58
	16.2	6.4 - 9.5		TAPD812BS							75786	2,000	6.33
	19.5	9.5 - 12.7		TAPD816BS							22730	2,000	6.50
	26.2	12.7 - 19.8		TAPD824BS							22234	2,000	7.36

d =Nominal Diameter, Min - Max Diameter; l =Body Length (+/- 0.5mm); g =Grip Range (Min - Max); d_h =Hole Size (Min - Max); d_k =Flange Diameter (Min - Max);
 k =Flange Thickness (Max); d_m =Nominal Mandrel Diameter; S =Nominal Shear Strength; T =Nominal Tensile Strength

The POP® Riveting Systems catalogue contains details of our core range only. Other rivet configurations are available. Please enquire to Emhart Customer Service. For the latest catalogue digital version please visit www.emhart.eu