

Micro Rivet
Domed Head

Aluminium 3.5% Magnesium Alloy
Mandrel: Carbon Steel



			DESCRIPTION							BULK PACK		
										ARTICLE	BOX QTY	
mm	mm	mm		mm	mm	mm	mm	N	N			kg
2.0 2.08 - 2.13	4.6	Up To 1.6	TAPD20M1BS	2.03 - 2.13	3.60 - 4.00	0.75	1.10	370	560	62996	1,000	0.43
	6.2	1.6 - 3.2	TAPD20M2BS							62997	1,000	0.46
	7.9	3.2 - 4.8	TAPD20M3BS							62998	1,000	0.50
	9.5	4.8 - 6.4	TAPD20M4BS							63132	1,000	0.54
	11.2	6.4 - 8.0	TAPD20M5BS							63118	1,000	0.57

d=Nominal Diameter, Min - Max Diameter; *l*=Body Length (+/- 0.5mm); *g*=Grip Range (Min - Max); *dh*=Hole Size (Min - Max); *dk*=Flange Diameter (Min - Max); *k*=Flange Thickness (Max); *dm*=Nominal Mandrel Diameter; *S*=Nominal Shear Strength; *T*=Nominal Tensile Strength

The POP® Riveting Systems catalogue contains details of our core range only. Other rivet configurations are available. Please enquire to Emhart Customer Service. For the latest catalogue digital version please visit www.emhart.eu