

Grooved Domed Head

Aluminium 3.5% Magnesium Alloy
Mandrel: Carbon Steel



			DESCRIPTION							BULK PACK		
										ARTICLE	BOX QTY	
mm	mm	mm		mm	mm	mm	mm	N	N			kg
3.3 3.30 - 3.45	9.7	-	TASD48BS	3.5 - 3.6	6.05 - 6.65	1.10	1.83	-	-	24657	10,000	1.07
4.1 4.00 - 4.28	7.0	-	TASD54BS	4.3 - 4.4	7.62 - 8.22	1.34	2.29	-	-	20387	8,000	1.60
	8.5	-	TASD56BS							24682	8,000	1.69
	12.1	-	TASD510BS							24658	5,000	2.02
5.0 4.85 - 5.15	7.9	-	TASD64BS	5.2 - 5.3	9.22 - 9.82	1.60	2.64	-	-	24926	5,000	2.37
	11.3	-	TASD68BS							24660	5,000	2.71
	13.4	-	TASD610BS							82582	5,000	2.80
	15.0	-	TASD612BS							24656	4,000	3.06
	19.5	-	TASD617BS							75385	4,000	3.23
	21.5	-	TASD621BS							70905	3,000	3.44
26.0	-	TASD625BS	24512	3,000	3.66							

d =Nominal Diameter, Min - Max Diameter; l =Body Length (+/- 0.5mm); g =Grip Range (Min - Max); d_h =Hole Size (Min - Max); d_k =Flange Diameter (Min - Max); k =Flange Thickness (Max); d_m =Nominal Mandrel Diameter; S =Nominal Shear Strength; T =Nominal Tensile Strength

The POP® Riveting Systems catalogue contains details of our core range only. Other rivet configurations are available. Please enquire to Emhart Customer Service. For the latest catalogue digital version please visit www.emhart.eu