











**Closed End
Domed Head**

Stainless Steel
Mandrel: Stainless Steel



 <i>d</i>	 <i>l</i>	 <i>g</i>	DESCRIPTION	 <i>d_h</i>	 <i>d_k</i>	 <i>k</i>	 <i>d_m</i>	 <i>S</i>	 <i>T</i>	BULK PACK		 /1,000 kg
										ARTICLE	BOX QTY	
mm	mm	mm		mm	mm	mm	mm	N	N			kg
3.2 3.15 - 3.28	6.6	Up To 1.6	TD42GT	3.3 - 3.4	6.12 - 6.65	0.87	2.00	2,100	2,220	76462	10,000	1.45
	8.0	1.6 - 3.2	TD44GT							82068	10,000	1.46
	9.7	3.2 - 4.8	TD46GT							82067	10,000	1.47
	11.3	4.8 - 6.4	TD48GT							82066	10,000	1.52
	12.9	6.4 - 7.9	TD410GT							78235	8,000	1.60
4.0 3.94 - 4.08	8.6	Up To 3.2	TD54GT	4.1 - 4.2	7.62 - 8.22	1.00	2.36	3,300	4,000	77425	6,000	2.30
	10.2	3.2 - 4.8	TD56GT							77424	6,000	2.36
	11.8	4.8 - 6.4	TD58GT							77423	6,000	2.41
	13.4	6.4 - 7.9	TD510GT							76463	5,000	2.47
4.8 4.73 - 4.88	9.2	Up To 3.2	TD64GT	4.9 - 5.0	9.23 - 9.83	1.25	2.97	4,300	4,400	77422	4,000	3.42
	10.8	3.2 - 4.8	TD66GT							77421	4,000	3.56
	12.5	4.8 - 6.4	TD68GT							77426	4,000	3.66
	15.5	6.4 - 9.5	TD612GT							77415	4,000	3.88
	18.5	9.5 - 12.7	TD616GT							76447	3,000	5.03
6.4 3.38 - 6.48	14.2	Up To 6.4	TD808GT	6.5 - 6.6	12.40 - 13.00	1.35	3.93	6,800	8,700	25870	2,000	7.13
	15.7	6.4 - 7.9	TD810GT							77427	1,500	8.43
	20.5	7.9 - 12.7	TD816GT							77428	1,500	9.03

d=Nominal Diameter, Min - Max Diameter; *l*=Body Length (+/- 0.5mm); *g*=Grip Range (Min - Max); *d_h*=Hole Size (Min - Max); *d_k*=Flange Diameter (Min - Max);
k=Flange Thickness (Max); *d_m*=Nominal Mandrel Diameter; *S*=Nominal Shear Strength; *T*=Nominal Tensile Strength

The POP® Riveting Systems catalogue contains details of our core range only. Other rivet configurations are available. Please enquire to Emhart Customer Service. For the latest catalogue digital version please visit www.emhart.eu