

Break Stem Open

Domed Head

Carbon Steel
Mandrel: Carbon Steel













			DESCRIPTION							BULK PACK		
										ARTICLE	BOX QTY	
mm	mm	mm		mm	mm	mm	mm	N	N			kg
2.8 2.73 - 2.88	5.3	0.5 - 2.9	TSPD33BS	2.9 - 3.0	5.24 - 5.84	1.32	1.83	715	930	78619	10,000	1.06
3.0 2.94 - 3.08	5.0	Up To 2.0	SNSD3050BS	3.1 - 3.2	5.70 - 6.30	1.10	1.83	1,100	1,400	78446	10,000	1.12
	6.5	2.0 - 3.5	SNSD3065BS							78441	10,000	1.18
	8.0	3.5 - 5.0	SNSD3080BS							78442	10,000	1.30
	10.0	5.0 - 7.0	SNSD3100BS							78443	10,000	1.47
	12.0	7.0 - 9.0	SNSD3120BS							78444	8,000	1.54
	15.0	9.0 - 12.0	SNSD3150BS							78445	5,000	1.70
3.2 3.10 - 3.28	4.5	Up To 1.6	TSPD42BS	3.3 - 3.4	6.05 - 6.65	1.10	1.93	1,150	1,550	81939	10,000	1.17
	6.0	1.6 - 3.2	TSPD44BS							81796	10,000	1.27
	8.0	3.2 - 4.8	TSPD46BS							81728	10,000	1.39
	9.5	4.8 - 6.4	TSPD48BS							75645	10,000	1.77
	11.5	6.4 - 7.9	TSPD410BS							77994	8,000	1.60
	13.5	7.9 - 9.5	TSPD412BS							75647	8,000	1.81
	15.0	9.5 - 11.1	TSPD414BS							81780	8,000	1.85
	17.0	11.1 - 12.7	TSPD416BS							81779	8,000	1.93
	19.0	12.7 - 14.3	TSPD418BS							77996	6,000	2.03
4.0 3.85 - 4.08	5.0	Up To 1.6	TSPD52BS	4.1 - 4.2	7.72 - 8.22	1.35	2.29	1,730	2,500	78719	6,000	2.00
	7.0	1.6 - 3.2	TSPD54BS							77932	6,000	2.10
	8.5	3.2 - 4.8	TSPD56BS							78009	6,000	2.22
	10.5	4.8 - 6.4	TSPD58BS							81789	5,000	2.45
	12.2	6.4 - 7.9	TSPD510BS							75650	5,000	2.62
	14.0	7.9 - 9.5	TSPD512BS							81769	5,000	2.78
	15.9	9.5 - 11.1	TSPD514BS							81768	5,000	2.99
	17.6	11.1 - 12.7	TSPD516BS							78004	4,000	3.18
	19.5	12.7 - 13.5	TSPD517BS							on request		3.27
	4.8 4.65 - 4.88	6.5	Up To 2.4							TSPD63BS	4.9 - 5.0	9.22 - 9.82
7.5		2.4 - 3.2	TSPD64BS	78042	4,000	3.40						
9.3		3.2 - 4.8	TSPD66BS	78049	4,000	3.55						
11.0		4.8 - 6.4	TSPD68BS	81727	4,000	3.88						
12.7		6.4 - 7.9	TSPD610BS	77939	3,000	4.00						
14.5		7.9 - 9.5	TSPD612BS	78032	3,000	4.53						
16.5		9.5 - 11.1	TSPD614BS	77942	3,000	4.67						
18.3		11.1 - 12.7	TSPD616BS	77944	3,000	4.83						
19.0		12.7 - 13.5	TSPD617BS	78038	3,000	4.90						
20.3		12.7 - 15.9	SD610BS	78518	2,000	4.00						
23.5		15.9 - 19.1	SD612BS	78519	2,500	4.44						
26.7		19.1 - 22.2	SD614BS	on request		5.36						
29.8		22.3 - 25.4	SD616BS	78520	2,000	6.25						

d =Nominal Diameter, Min - Max Diameter; l =Body Length (+/- 0.5mm); g =Grip Range (Min - Max); d_h =Hole Size (Min - Max); d_k =Flange Diameter (Min - Max); k =Flange Thickness (Max); d_m =Nominal Mandrel Diameter; S =Nominal Shear Strength; T =Nominal Tensile Strength

The POP® Riveting Systems catalogue contains details of our core range only. Other rivet configurations are available. Please enquire to Emhart Customer Service. For the latest catalogue digital version please visit www.emhart.eu

**Break Stem Open
Domed Head**

Carbon Steel
Mandrel: Carbon Steel

				DESCRIPTION							BULK PACK		
											ARTICLE	BOX QTY	
	mm	mm	mm		mm	mm	mm	mm	N	N			kg
5.0 4.85 - 5.08	6.5	Up To 2.5		SNSD5065BS	5.1 - 5.2	8.70 - 9.30	1.60	2.90	2,880	3,790	77928	4,000	3.40
	8.0	2.5 - 4.0		SNSD5080BS							78463	4,000	3.55
	10.5	4.0 - 6.0		SNSD5100BS							78464	4,000	3.88
	12.0	6.0 - 8.0		SNSD5120BS							78468	3,000	4.00
	14.0	8.0 - 10.0		SNSD5140BS							78469	3,000	4.43
	16.0	10.0 - 12.0		SNSD5160BS							78470	3,000	4.67
	18.0	12.0 - 14.0		SNSD5180BS							78471	3,000	4.83
	22.0	16.0 - 18.0		SNSD5220BS							on request		5.17
6.0 5.85 - 6.08	8.0	Up To 2.0		SNSD6080BS	6.1 - 6.2	11.70 - 12.30	2.10	3.65	4,200	5,500	on request		6.40
	10.0	2.0 - 4.0		SNSD6100BS							78450	2,000	6.74
	12.0	4.0 - 6.0		SNSD6120BS							78452	2,000	7.56
	14.0	6.0 - 8.0		SNSD6140BS							78454	2,000	7.70
	16.0	8.0 - 10.0		SNSD6160BS							on request		7.88
	18.0	10.0 - 12.0		SNSD6180BS							on request		8.02
	20.0	12.0 - 14.0		SNSD6200BS							on request		8.20
	6.4 6.40 - 6.51	9.5	0.5 - 3.8								TSPD8095BS	6.53 - 6.63	10.55 - 11.15
13.0		3.8 - 7.6		TSPD8130BS	78586	1,500	8.25						
18.5		7.6 - 12.7		TSPD8185BS	78607	1,500	8.47						
21.6		12.7 - 15.9		SD810BS	78521	1,000	9.20						
24.8		15.9 - 19.1		SD812BS	78522	1,000	9.92						
27.9		19.1 - 22.2		SD814BS	on request		10.60						
31.1		22.2 - 25.4		SD816BS	78562	1,000	11.30						

d=Nominal Diameter, Min - Max Diameter; *l*=Body Length (+/- 0.5mm); *g*=Grip Range (Min - Max); *d_h*=Hole Size (Min - Max); *d_k*=Flange Diameter (Min - Max); *k*=Flange Thickness (Max); *d_m*=Nominal Mandrel Diameter; *S*=Nominal Shear Strength; *T*=Nominal Tensile Strength

The POP® Riveting Systems catalogue contains details of our core range only. Other rivet configurations are available. Please enquire to Emhart Customer Service. For the latest catalogue digital version please visit www.emhart.eu