




TVD Closed End

Domed Head

Stainless Steel

Mandrel: Stainless Steel



			DESCRIPTION							BULK PACK		
d	l	g		d _h	d _k	k	d _m	S	T	ARTICLE	BOX QTY	/1,000
mm	mm	mm		mm	mm	mm	mm	N	N			kg
4.0 3.94 - 4.08	12.9	4.0 - 6.0	TVD505GT	4.1 - 4.2	7.37 - 8.22	1.1	2.29	3,000	3,000	78231	6,000	2.43
4.8 4.73 - 4.88	12.3	2.0 - 4.5	TVD603GT	5.0 - 5.1	9.10 - 9.95	1.25	2.97	4,300	4,800	77695	4,000	3.75
	13.7	3.5 - 6.0	TVD605GT							76897	3,000	3.83
	15.3	5.0 - 7.5	TVD607GT							77697	3,000	4.87
	16.8	6.5 - 9.0	TVD609GT							77698	3,000	4.80
	19.7	9.0 - 11.5	TVD613GT							77699	3,000	5.13

d=Nominal Diameter, Min - Max Diameter; *l*=Body Length (+/- 0.5mm); *g*=Grip Range (Min - Max); *d_h*=Hole Size (Min - Max); *d_k*=Flange Diameter (Min - Max); *k*=Flange Thickness (Max); *d_m*=Nominal Mandrel Diameter; *S*=Nominal Shear Strength; *T*=Nominal Tensile Strength

The POP® Riveting Systems catalogue contains details of our core range only. Other rivet configurations are available. Please enquire to Emhart Customer Service. For the latest catalogue digital version please visit www.emhart.eu