

Vgrip™ Domed Head

Aluminium 2.5% Magnesium Alloy
Mandrel: Carbon Steel



			DESCRIPTION							BULK PACK		
					ARTICLE	BOX QTY	kg					
mm	mm	mm		mm	mm	mm	mm	N	N			kg
4.8	10.8	1.5 - 6.0	VG11-04810-511	4.9 - 5.0	9.22 - 9.82	1.6	3.0	1,200	1,900	79200	5,000	3.15
	16.5	6.0 - 10.0	VG11-04816-511	4.9 - 5.0	9.22 - 9.82	1.6	3.0	1,200	1,900	79201	4,000	4.26

Vgrip™ Large Flange

Aluminium 2.5% Magnesium Alloy
Mandrel: Carbon Steel



			DESCRIPTION							BULK PACK		
					ARTICLE	BOX QTY	kg					
mm	mm	mm		mm	mm	mm	mm	N	N			kg
4.8	10.8	1.5 - 6.0	VG12-04810-511	4.9 - 5.0	15.7 - 16.3	2.1	3.0	1,200	1,900	79202	4,000	3.71
	16.5	6.0 - 10.0	VG12-04816-511	4.9 - 5.0	15.7 - 16.3	2.1	3.0	1,200	1,900	79203	3,000	4.28

d =Nominal Diameter, Min - Max Diameter; l =Body Length (+/- 0.5mm); g =Grip Range (Min - Max); d_h =Hole Size (Min - Max); d_k =Flange Diameter (Min - Max); k =Flange Thickness (Max); d_m =Nominal Mandrel Diameter; S =Nominal Shear Strength; T =Nominal Tensile Strength

The POP® Riveting Systems catalogue contains details of our core range only. Other rivet configurations are available. Please enquire to Emhart Customer Service. For the latest catalogue digital version please visit www.emhart.eu