

WellNut®



Standard Flange

- Ideal for general purpose use, where dampening of vibration and shock is required

M	g	DESCRIPTION	d_h	l	d_k	k	d	tt	BULK PACK		SMALL PACK		KG /1,000
									ARTICLE	BOX QTY	ARTICLE	BOX QTY	
			mm	mm	mm	mm	mm	Nm					kg
M3	0.4 - 4.0	WNPA-0311-E632	8.0	12.6	11.0	1.2	7.9	0.4	63537	7,500	63538	100	
M4	0.4 - 4.0	WNPA-0411-B832	8.0	12.6	11.0	1.2	7.9	0.3	63539	7,800	63540	100	
M5	0.4 - 4.9	WNPA-0514-10S	9.7	14.1	12.7	0.9	9.6	0.4	63541	4,700	63542	100	
	0.9 - 5.9	WNPA-0516-Q1032	9.7	17.0	14.0	1.0	9.6	0.5	63543	3,800	63544	100	
	4.0 - 10.0	WNPA-0521-H1032	9.7	21.5	14.0	0.9	9.6	0.6	63545	3,000	63546	100	
	7.9 - 15.0	WNPA-0525-10SL	9.7	26.5	14.0	1.3	9.6	0.5	63547	2,200	63548	100	
M6	0.4 - 4.0	WNPA-0615-1/4S	12.8	16.0	16.0	1.3	12.7	0.8	63551	2,500	63552	100	
	4.7 - 8.7	WNPA-0619-W1420	12.8	20.3	16.0	1.3	12.7	0.8	63553	2,000	63554	100	
	6.4 - 11.5	WNPA-0625-J1420	12.8	26.7	16.3	2.0	12.7	0.9	63555	1,300	63556	100	
M8	0.4 - 4.0	WNPA-0815-E51618	16.0	18.3	21.5	3.2	15.9	1.2	63557	1,200	63558	100	



Large Flange

- Large flange feature increases the bearing surface for weaker/thinner materials

M	g	DESCRIPTION	d_h	l	d_k	k	d	tt	BULK PACK		SMALL PACK		KG /1,000
									ARTICLE	BOX QTY	ARTICLE	BOX QTY	
			mm	mm	mm	mm	mm	Nm					kg
M3	9.5 - 13.0	WNPL-0324-C632	6.2	24.9	14.0	0.9	6.1	0.4	63559	4,000	63560	100	
M4	0.4 - 4.4	WNPL-0413-C832	8.0	14.2	19.1	1.5	7.9	0.3	63561	3,300	63562	100	
M5	0.8 - 5.8	WNPL-0516-G1032	9.7	21.0	19.0	4.7	9.6	0.5	63563	1,800	63564	100	
	0.8 - 5.8	WNPL-0516-J1032	9.7	18.0	19.0	2.0	9.6	0.5	63565	2,500	63566	100	
M6	0.8 - 4.7	WNPL-0615-D1420	12.8	21.1	19.1	4.8	12.7	0.9	63567	1,600	63568	100	

M=Thread Size; l=Nominal Body Length; g=Grip Range (Min - Max); d_h =Hole Size; d_k =Nominal Head Diameter; k=Nominal Head Thickness; d=Nominal Barrel Diameter; tt=Nominal Tightening Torque