

Technical drawing of a mechanical part, likely a bracket or arm, showing dimensions and tolerances.

Main View Dimensions:

- Total length: $721,0 \pm 2$ mm
- Offset at each end: 15,0 mm
- Central section length: 330,0 mm
- Section with holes length: 361,0 mm
- End view radius: $R7,5$
- End view height: 15 mm
- Central section diameter: $\varnothing 8$
- Hole diameter: $\varnothing 18^{+1}_{-0,2}$

Bottom View Dimensions:

- Thickness: $5^{+0,3}_{-0,1}$ mm
- Offset: $5^{+0,3}_{-0,1}$ mm
- Inner diameter: $\varnothing 8,1^{+0,3}_{-0,1}$ mm

Kräfte statisch gemessen bei 20°C im 2. Lastwechsel
mit Kolbenstange nach unten zeigend
static force measurement at 20°C on second cycle
with piston rod down

200 < F1 ≤ 1000: -20+40
1000 < F1 ≤ 2000: -50+50
F1 > 2000: -100+100

Einbau mit Kolbenstange nach unten zeigend,
hierdurch Wirksamkeit der hydraulischen Dämpfung /
Installation with piston rod down to effect hydraulic damping

Einsatzmöglichkeit / operating temperature: -30°C bis/to +80°C

Liftline-Normen / Standards: AW GF 016



in	401,0 mm
out	721,0 mm
MP	5,0 mm
MH	320,0 mm



Customer

Date of creation

Spring description

16-2-361-330-A23-B23